

## **KHP 135 II, KHP 210 II**

Kent compactor/drivers combine high frequency vibration with high impact power to make quick work of any compaction or driving task.

Designed for use on medium and large excavators, these compactors are designed to work anywhere a boom can reach – in trenches, around foundations, on slopes or seawalls. Hydra-Paks can safely compact trenches, often eliminating the extra cost involved with a man and walk-behind unit and the added expense of trench boxes or shoring. The Hydra-Paks are also ideal for driving steel sheeting used for retaining walls.

Kent compactor/drivers feature special rubber shock absorbers which protect the boom by isolating it from the Hydra-Pak vibrations and a cross-over check valve protects the motor.

Kent KHP 135 II delivers 13,500 lbs. of impulse force and the KHP 210 Ft II delivers 21,00 lbs. of impulse force at 2000 cycles per minute assuring maximum lift capacity. All units are built for rugged, reliable performance with hardened steel components to resist the effects of stress, vibration, fatigue and impact forces.



*KHP 135 II*

*KHP 210 Ft II*





# KHP 135 II

# KHP 210 II

## SPECIFICATIONS

## MODEL

	KHP 135 II	KHP 135 Ft II	KHP 210 II	KHP 210 Ft II
Impulse Force lbs. (kg)	13,500 (6124)	13,500 (6124)	21,000 (9525)	21,000 (9525)
Cycles Per Minute	2,000	2,000	2,000	2,000
Operating Pressure PSI (BAR)	2,000 (138)	2,000 (138)	2,000 (138)	2,000 (138)
Hydraulic Flow Req'd GPM (LPM)	30 (114)	30 (114)	48 (182)	48 (182)
Weight lbs. (kg)*	1,335 (606)	1,400 (635)	2,150 (975)	2,180 (989)
Height In. (mm)*	34 (864)	27 (686)	39.5 (1003)	32 (813)
Width In. (mm)	28 (711)	28 (711)	34 (864)	34 (864)
Pin Spacing In. (mm)	19.5 (495)	O.E.M.	19.5 (495)	O.E.M.
Mounting Pin Diameter	As required	As required	As required	As required
Base Plate Dimensions In. (mm)	28 x 40 (711 x 1,016)	28 x 40 (711 x 1,016)	34 x 46 (864 x 1,168)	34 x 46 (864 x 1,168)
Compaction Area sq. ft. (sq. m)	7.8 (.72)	7.8 (.72)	10.8 (1.0)	10.8 (1.0)
Hose Size In. (mm)				
Pressure Line In. (mm)	0.75 (19)	0.75 (19)	1 (25)	1 (25)
Return Line In. (mm)	1 (25)	1 (25)	1.25 (32)	1.25 (32)

\* Weight does not include pins and bushings for all models or bolt-on top cap for Ft models

### Features and Benefits:

- Eliminates costly trench boxes and shoring
- Drives sheeting for retaining walls
- Rubber shocks absorb vibration protecting the carrier's boom
- Available with O.E.M. bolt-on top cap



711 Lake Street • Kent, OH 44240  
 330-673-5826 • Fax: 330-677-1616  
 Toll Free: 1-800-527-2282 (East Coast)  
 1-800-624-1616 (West Coast)

[www.kentdemolition.com](http://www.kentdemolition.com)